

## **REBOKE INOX**

Fast transport of grains  
and fertilisers



## REBOKE STAINLESS STEEL

# + UNLOADING AGILITY

Reboke Inox (Stainless steel) grain carts are engineered to transport grains and fertiliser. The transport and loading of grains and fertiliser are fast and safe.

### Unloading tube

Unloading tube of **400 mm** with unloading capacity of up to

# 5500 kg/min\*

The unloading of fertilisers is of up to **3,500 kg/min\*** and faster. It features two augers only and angle alignment between the two stages of the auger that allows the operator to have a clearer grain unloading view. Polymer unloading tube that ensures more durability and easy maintenance.

*\* It depends on the equipment model, product type, density, and moisture.*

## THE GREATEST TURNING RADIUS

It features the greatest turning radius of its category, which eases crop steering operations and avoids steering system damages.

### Directional unloading tube spout

Reboke Inox is equipped with a directional spout that improves the grain unloading onto the lorry. Polyethylene spout that ensures durability and easy maintenance.

### Telescopic tube

It was engineered to assist in fertiliser loading onto the planter hopper without wasting products. The tube is divided into 3 sections that extend or retract its extension as needed.

### Transmission system

Electromagnetic clutch for operations with flow of up to **1500 kg/min** that eases the operator work when loading the planters. Transmission system for high-flow operations of up to **3500 kg/min** to load spreaders and ensure fast operations.

## REBOKE 30000 INOX (STAINLESS STEEL)

# LOAD CAPACITY 30 m<sup>3</sup>



### Hopper

It is made of stainless steel to be high-resistant to corrosion caused by fertilizers. It also increases the grain cart durability.

### Tyres

High fluctuation pressure tyres\* that avoid soil compaction during grains and fertilisers transport.

*\* Optional feature for Reboke 15000 Inox, Reboke 20000 Inox, and Reboke 25000 Inox.*



**REBOKE 25000 INOX  
(STAINLESS STEEL)  
LOAD  
CAPACITY **25** m<sup>3</sup>**



**REBOKE 20000 INOX  
(STAINLESS STEEL)  
LOAD  
CAPACITY **20** m<sup>3</sup>**



**REBOKE 15000 INOX  
(STAINLESS STEEL)  
LOAD  
CAPACITY **15** m<sup>3</sup>**

## TECHNICAL SPECIFICATIONS

Model	Reboke 15000 Stainless steel	Reboke 20000 Stainless steel	Reboke 25000 Stainless steel	Reboke 30000 Stainless steel
<b>Load volume</b>				
15 m <sup>3</sup>	20 m <sup>3</sup>	25 m <sup>3</sup>	30 m <sup>3</sup>	
<b>Maximum load capacity</b>				
16,500 kg	22,000 kg	27,500 kg	33,000 kg	
<b>Diameter of the unloading tube</b>				
400 mm	400 mm	400 mm	400 mm	
<b>Standard wheelset</b>				
30.5-32 x 2	23.1-26 x 4	30.5-32 x 4	850/50R-30.5 x 4	
<b>Optional wheelset</b>				
850/50R 30.5 x 2	650/65R30.5 x 4   23.1 - 30x4	650/65R30.5 x 4   23.1 - 30x4	-	
<b>Tail light</b>				
Serial	Serial	Serial	Serial	
<b>Directional unloading tube spout</b>				
Serial	Serial	Serial	Serial	
<b>Telescopic tube</b>				
Serial	Serial	Serial	Serial	
<b>*Unloading height</b>				
4,700 mm	4,700 mm	4,700 mm	4,700 mm	
<b>Unloading drive</b>				
Tractor power take-off	Tractor power take-off	Tractor power take-off	Tractor power take-off	
<b>Optional items</b>				
Retractable roll tarp	Retractable roll tarp	Retractable roll tarp	Retractable roll tarp	
Brake	Brake	Brake	Brake	
Electromagnetic clutch	Electromagnetic clutch	Electromagnetic clutch	Electromagnetic clutch	
Grille	Grille	Grille	Grille	
	Semi trailer hitch kit	Semi trailer hitch kit	Semi trailer hitch kit	
	Electronic scale kit	Electronic scale kit	Electronic scale kit	

\*Approximate height with standard wheelset

## LEARN MORE

Position your mobile phone on QR code to read it and check it out!

### Video

See for yourself, Reboke Inox operation quality in the crop field.



### Website

Access Reboke Inox homepage on Stara website for more information.



THIS SPACE IS INTENDED FOR DEALERSHIP DATA

[www.stara.com.ar](http://www.stara.com.ar)

Stara Argentina | Micro Parque Industrial - KM 280,5 Ruta 9, Alvear - Santa Fé - Argentina | Phone number: 54 341 558 2800 | Email address: [hableconnosotros@stara.com.ar](mailto:hableconnosotros@stara.com.ar)

[LinkedIn/company/Stara](#) - [YouTube/StaraConstantEvolution](#) - [Facebook/StaraArgentina](#) - [Instagram/staraargentina](#)